

JAPANESE PATENT OFFICE
PATENT JOURNAL
KOKAI PATENT APPLICATION NO. SHO 59[1984]-117252

| | |
|-------------------------------|--------------------------------|
| Int. Cl. ³ : | H 01 L 23/48 23/52 25/02 |
| Sequence Nos. for Office Use: | 6819-5F 6428-5F 7638-54 |
| Application No.: | Sho 57[1982]-226308 |
| Application Date: | December 24, 1982 |
| Publication Date: | July 6, 1984 |
| No. of Claims: | 1 (Total of 4 pages) |
| Examination Request: | Not requested |

SEMICONDUCTOR DEVICE

| | |
|------------|--|
| Inventors: | June Morishita Hitachi Microcomputer Engineering, Co., Ltd. 1479 Kamimimoto-cho, Kodaira-shi |
| | Kazuyoshi Sato Device Development Center, Hitachi, Ltd. 1450 Kamimimoto-cho, Kodaira-shi |

Yoshihisa Takeno
Device Development
Center, Hitachi, Ltd.
1450 Kamimimoto-cho,
Kodaira-shi

Applicants:

Hitachi Microcomputer
Engineering Co., Ltd.
1479 Kamimimoto-cho,
Kodaira-shi

Hitachi Ltd.
1-5-1 Marunouchi,
Chiyoda-ku, Tokyo

Agent:

Toshiyuki Usuda,
patent attorney

[There are no amendments to this patent.]

Claims

1. A semiconductor device characterized by a construction in which more than two kinds of buds are installed to one semiconductor pallet, with one being a dummy bud for testing.

2. A semiconductor device described in Claim 1, characterized by a construction in which the dummy buds are arranged around the edge of the semiconductor pallet.

* * *